

Reliable exam torrent & valid VCE PDF materials & dumps torrent files

Input your exam code ...



Our high-quality valid VCE PDF materials & dumps torrent files guarantee you pass exam 100% for sure. Our reliable exam torrent will be the best help for your exams and will give you a new start, a new life.

All Products

Contact now



Quality and Value

VCETorrent Practice Exams are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development - no all dumps.



Tested and Approved

We are committed to the process of vendor and third party approvals. We believe professionals and executives alike deserve the confidence of quality coverage these authorizations provide.



Easy to Pass

If you prepare for the exams using our VCETorrent testing engine, It is easy to succeed for all certifications in the first attempt. You don't have to deal with all dumps or any free torrent / rapidshare all stuff.



Try Before Buy

VCETorrent offers free demo of each product. You can check out the interface, question quality and usability of our practice exams before you decide to buy.

19728

CUSTOMERS

32727

DOWNLOADS

21728

TEAM MEMBERS

26394

SHARES

<http://www.vcetorrent.com>

Reliable exam torrent & valid VCE PDF materials & dumps torrent files

Exam : **H12-223**

Title : Huawei Certified Network
Professional-R&S-IEEP

Vendor : Huawei

Version : DEMO

NO.1 Which of the following aspects should be considered during preliminary analysis of a migration project?

(Multiple Choice)

- A. Necessity
- B. Risks
- C. Costs
- D. Feasibility

Answer: A,B,D

NO.2 Which of the following scenarios is a loop test applicable to?

- A. To test whether a physical link is disconnected
- B. To test whether a switch can prevent loops and broadcast
- C. To test whether applications are properly connected
- D. To test whether a routing protocol can prevent loops

Answer: A

NO.3 Which of the following operations is unnecessary to resolve a failure for hosts in the same VLAN to communicate with each other?

- A. Run the display current-configuration command to check the PCB version and the software version of a card.
- B. Run the display interface interface-type interface-number command in any view to check the status of communication interfaces.
- C. Run the display vlan vlan-id command in any view to check whether the VLAN for communication interfaces has been created.
- D. Run the display mac-address command on the switch to check MAC address entries including the MAC address, port number, and VLAN ID.

Answer: A

NO.4 If a fault cannot be rectified in a short time on a complex network but the customer needs to restore network availability immediately, which of the following actions is recommended?

- A. Attempt to rectify the fault. If the fault cannot be rectified after a period of time, communicate with the customer.
- B. Tell the customer that this is impossible.
- C. Set up an alternative network environment.
- D. Communicate with the customer on skipping the faulty node, and set up an alternative network environment.

Answer: D

NO.5 Which of the following network features is described by counters such as mean time between failures (MTBF) and mean time to repair (MTTR)?

- A. Cost-effectiveness
- B. Availability
- C. Security

D. Scalability

Answer: B

NO.6 Current enterprise networks usually use OSPF as the routing protocol. What precautions are there when OSPF is used? (Multiple Choice)

- A.** Determine that the backbone area will not split.
- B.** Check whether secondary optimal routes exist on the network according to OSPF route selection rules.
- C.** Check the OSPF network topology and ensure that no loop exists when OSPF routes are being calculated.
- D.** Check whether all non-backbone areas are correctly and reliably connected to the backbone area.
- E.** Verify that OSPF costs can correctly demonstrate the actual bandwidth of links at more than 100 Mbit/s.

Answer: A,B,D,E

NO.7 During follow-up operations of the structured network troubleshooting process, which of the following documents need to be transferred? (Multiple Choice)

- A.** Troubleshooting intermediate documents
- B.** User communication plan
- C.** Troubleshooting summary report
- D.** Change backup and maintenance suggestions

Answer: A,C,D

NO.8 Which of the following networks are involved during construction of a large enterprise network? (Multiple Choice)

- A.** Storage network
- B.** Transport network
- C.** Data center network
- D.** Wireless network
- E.** Backbone network

Answer: C,D,E

NO.9 During the structured network troubleshooting process, which of the following items require attention in the information collection phase? (Multiple Choice)

- A.** How to collect information
- B.** What information to collect
- C.** Risks in the information collection phase
- D.** Whether authorization is required

Answer: A,B,C,D

NO.10 To rectify a VRRP group two-master fault, run the display this command on VLANIF interfaces on both ends of the VRRP group. Which of the following operations is not performed?

- A.** Check whether the virtual IP address is the same on the VLANIF interfaces in the VRRP group.

- B. Check whether the interface IP addresses are on the same network segment.
- C. Check whether the VLANIF interfaces have the same VRRP group ID.
- D. You do not need to check whether the interval for sending VRRP Advertisement packets is the same on the VLANIF interfaces.

Answer: D

NO.11 Which of the following are possible causes for an MSTP failure in a LAN? (Multiple Choice)

- A. A physical link alternates between Up and Down, triggering the device to send a large number of TC packets.
- B. MSTP is configured incorrectly.
- C. The priority of the port in the specified MSTE is not configured.
- D. The MSTP-enabled device receives MSTPTC packets that are transparently sent or from the client.

Answer: A,B,D

NO.12 As shown in the figure, all interfaces of the router have ospf enabled. Which one of the following descriptions is correct?

- A. R5 will generate Type3 LSA in area 1
- B. The Type3 LSA generated by R3 in area 0 contains 10.0.2.2/32 routing information
- C. The Type3 LSA generated by R4 in area 1 contains 10.0.2.2/32 routing information
- D. The Type3LSA generated by R6 in area 1 contains 10.0.2.2/32 routing information

Answer: C

NO.13 When a large number of IP phones and WLAN APs exist on a network, which of the following switches is used?

- A. Switches supporting STP edge ports
- B. Switches supporting PoE
- C. Switches supporting SACG
- D. Switches supporting QoS

Answer: B

NO.14 If a fault is located on a router that works in redundancy mode with another router, which of the following methods is the most appropriate for subsequent troubleshooting?

- A. Top-down
- B. Bottom-up
- C. Configuration comparison
- D. Service traffic path check

Answer: C

NO.15 Which of the following line interface types belongs to a different category from other interface types?

- A. SC interface
- B. FC interface
- C. LC interface

D. BNC interface

Answer: D